

FS1/240v

Hand Carry Frame
1 x 9788 Super Duty Filter Unit
Gear pump -
240v motor
Safety by pass valve
Pressure gauge
Isolator On/Off switch
3 metre suction and return lines.
Height 700 mm
Base 270 x 350 mm
Weight 18kilo



Filtration Units

A simple free-standing, offline, fluid cleaning rig, used as a multipurpose cleaner or transfer unit. Standard configuration single pot filtration unit.

An 18k hand carry frame fitted with required pump range and 240 volt motor, (can add 110v) single 9788 filter unit with cartridge mounted with isolator on/off switch, pressure overload cut out switch, pressure gauge, and 3 metre suction and return lines, supplied complete and ready to use.

- Single unit rig will process approximately 250 ltrs per hour dependant on temperature and viscosity.
- Longer hose assemblies available.
- Unit supplied ready to use.

Filter Cartridges

Filter cartridges are 3 micron absolute and filter to 1 micron, and will remove approx 1litre of water per cartridge and up to 2 kgs of dirt. They are manufactured from tightly wound cellulose impregnated long fibre paper. Polypropylene filters are available to filter all water and glycol based oils and fluids. Based on normal use the average life span of cartridges under standard operating conditions will give 250-300 hours of continuous use.

Single unit rig will process approximately 300-500 litres per hour dependant on temperature and viscosity.

Oil Flow Rate: Output levels are dependent on viscosity, temperature, degree of contamination, and oil pressure.

Warranty 12 months on all parts.

Full instruction manual and parts listing.

All Rigs are built to order, available within 5 to 10 working days.

UK Manufactured